SSL310BF SMBF

Surface Mount Schottky Barrier Rectifier

Reverse Voltage - 100 V

Forward Current - 3 A

Pinning

1.Cathode	2.Anode



SMBF

YFW SL310B

FEATURES

Metal silicon junction, majority carrier conduction

For surface mounted applications

Low power loss, high efficiency

High forward surge current capability

For use in low voltage, high frequency inverters,

free wheeling, and polarity protection applications

Lead free in comply with EU RoHS 2011/65/EU directives

MECHANICAL DATA

Case: SMBF

Terminals: Solderable per MIL-STD-750, Method 2026

Approx. Weight: 57mg /0.002oz

Absolute Maximum Ratings and Electrical characteristics

Ratings at 25 ° ambient temperature unless otherwise specified.Single phase, half wave, 60HZ, resistive or inductive load. For capacitive load, derate current by 20%

Marking Diagram

Ordering information

Package	Packing Description	Packing Quantity
SMBF	Tape/Reel,13”reel	5000PCS/Reel 50000PCS/Carton

Package Dimensions

SMBF

	Dim.	Millimeter(mm)		mil	
		Min.	Max.	Min.	Max.
	A	1.1	1.		

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website https://www.yfwdiode.com, or consult YFW sales office for further assistance. ㇔ ㇔ .