!7@>#?231B2?-#C09C#B1=>792#/01/2@#

"2B2?@2#D1=>792#E#F)GD#

!1?+7?/# 6??28>#E(HH4 I#

!<IJK"<L#

- Supersmall size
- High reliability
- High speed switching

M< NIOP I #$IJI#

- Case: Molded Plastic Body
- Epoxy meets UL 94V-0 flammability rating
- Terminals: Pure tin plated leads, solderable per J-STD-002and JESD22-B102, E3 suffix for consumer grade, meet JESD201class 1A whisker test.
- Polarity: Color band denotes cathode end

M7Q04 6 4#?7>089#RJ7S)T #68=2@@#1>C2?+0@2#81>2/U

V7?7 4 2>2?#		L-4W1=#	!"#	K80>#
Repetitive peak reverse voltage		D""M#	35	XD#
Average forward current	60H_Z half-sine wave, Resistance load, Ta=25°C	P!RID0#	100	4 I#
Surge(Non-repetitive)forward current	60H_Z half-sine wave,1cycle,T_a=25°C	P!LM#	15	I#

Peak forward voltag1c

Ordering information

Package	Packing Description	Packing Quantity

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed heN ɨ ɨ ɨ duy fo u. c a ɔ N