

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V_{RM}	100	V
Reverse Voltage	V_R	80	V
Average Rectified Forward Current	$I_{F(AV)}$	150	mA
Forward Continuous Current	I_{FM}	300	mA
Non-Repetitive Peak Forward Surge Current (at t = 1 µs)	I_{FSM}	0.5	A
Power Dissipation	P_d	200	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	- 65 to + 150	°C

Parameter	Symbol	Min.	Max.	Unit
Forward Voltage at I_F = 5 mA at I_F = 10 mA at I_F = 100 mA at I_F = 150 mA	V_F	 0.62 - - -	 0.72 0.855 1 1.25	V
Reverse Leakage Current at V_R = 80 V at V_R = 20 V at V_R = 75 V, T_J = 150 °C at V_R = 25 V, T_J = 150 °C	I_R	 - - - -	 100 25 50 30	 nA nA µA µA
Reverse Breakdown Voltage at I_R = 100 µA	$V_{(BR)R}$	80	-	V
Total Capacitance at V_R = 0.5 V, f = 1 MHz	C_{tot}	-	4	pF
Reverse Recovery Time at $I_F = I_R$ = 10 mA, I_{rr} = 0.1 X I_R , R_L = 100 Ω	t_{rr}	-	4	ns


300
200
100
DISSIPATION, MILLIWATTS
100
10
Ta = 25°C
Ta = 50°C
Ta = 85°C
Ta = -30°C
POWER

Ordering information

Package

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its . or l' re-