- Low cost
- Diffused junction
- Low Leakage
- Low forward voltage drop
- High current capability
- Easily cleaned with Freon. Alcohol. Lsopropanol and solvents
- The plastic material carries U/L recognition 94V-O

- Case : R-6
- Terminals: Axial leads. Solderable per MIL - STD - 202. Method 208
- Polarity: Color band denotes cathode
- Mounting Position : Any
- Weight : 0.072 ounce, 2.05 grams

Ratings at 25 ambient temperature unless otherwise specified.
Single phase. half wave. 60HZ. resistive or inductive load. For capacitive load. derate current by 20

μ

Ordering information

Package	Packing Description	Packing Quantity
R-6		

Package Dimensions

R-6

	Dim.	Millimeter(mm)		INCHES	
		Min.	Max.	Min.	Max.

The information presented in this document is for reference only. GuangDong Youfeng Microelectronics Co.,Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise. The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices),YFW or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale. This publication supersedes & replaces all information previously supplied. For additional information, please visit our website https://www.yfwdiode.com, or consult YFW sales office for further assistance.